

Surge Test Data

Applicant : <u>明威</u>											
EUT : <u>面板灯</u>				M/N : <u>BP3378A+BP5001</u>							
Power Supply: <u>AC 230/50HZ</u>											
Repetition : <u>5</u> times pre test						Interval : <u>60</u> seconds					
Performance Criteria : <u>B</u>											
Ambient Condition : <u>25</u> °C <u>55</u> %RH											
Operation Mode : <u>Lighting</u>											
Test standard: <u>EN61547</u>						Test result: <u>Pass</u>					
Line : <input checked="" type="checkbox"/> AC Mains <input type="checkbox"/> DC Mains <input type="checkbox"/> Signal : _____											
Location	Voltage	1 KV		2 KV		3 KV		4 KV		5 KV	
	Phase	+	-	+	-	+	-	+	-	+	-
L-N	0°										
	90°	Pass									
	180°										
	270°		Pass								
L-PE	0°										
	90°										
	180°										
	270°										
N-PE	0°										
	90°										
	180°										
	270°										
DC Supply											
Signal Line											
Telecommunication Line											
Note : 在产品正常工作后, 根据测试标准, 对样品进行浪涌测试。L-N 测试电压为±1KV, 样品从测试到结束无常。测试产品符合测试标准要求。故测试通过。											

Approved By : _____

Tested By : W.H

Date : 2017-9-20

